

CS-61 Multicast LMR Remote

At A Glance

Multicast LMR Remote- The CS-61 is an economical solution for enabling a single channel of Push to Talk capability for LMR applications using standards based multicast protocol.



All New Design

- Breakthrough Purpose built PTT Device
- Single channel Multicast end point
- Standards based multicast protocol
- Compact Design for Maximum Portability
- Simple to Set up & Use
- Microphone, handset or headset options
- Rotary volume control for ease of use
- PoE & Local power options

Technologically Advanced

- Native 1-channel Multicast Device
- Supported Codecs: G.711 A/uLaw, G.729
- Static / DHCP / Remote Configuration
- Browser based administration
- Secure administrative access
- Station to station latency less than 55ms



A Veteran Owned Small Business

Technical Specifications

Channels

- (1) Multicast group

Call Types

- Multicast, Radio Conferencing
- Push to Talk Broadcast

Mode of Operation

- Multicast IP Audio Broadcast

Interfaces


- 12" Gooseneck Microphone
- Handset w/PTT (RJ-25)
- Mono Headset (RJ-25)
- (1) Ethernet Port

Dimensions

- Width - 4" / 102mm
- Depth - 5.5" / 140mm
- Height - 5.5" / 140mm
- Weight - 1.1 lbs / 525 g
- 12" / 305mm - Gooseneck microphone

Codec Options (bandwidth including overhead)

- | | |
|-----------------|---------|
| ■ G.711 a/u-law | 80 kbit |
| ■ G.729 | 20 kbit |



Management

- Browser based, Internet Explorer, Google Chrome
- Upgradeable application firmware via file upload

Power

- 48 VDC, 1/2 A, External PoE Injector
- 48 VDC, IEEE 802.3af, Alt A & B, Power over Ethernet

Thermal

- 3 Watts
- 10 BTU/hr
- Cooling - Ambient air

Network Requirements

- 100 Base T (full duplex)
- IEEE 802.3af (PoE) compliant
- Protocols - UDP, DHCP, DNS, Syslog, NTP, SSH, TCP
- Multicast Latency - less than 55ms