


VCC-3™ USB Command Console



Overview

The VCC-3™ is a USB Microphone Console specifically designed for use with inter-operability applications such as Motorola Solutions, SmartPTT, Skytec, *TRBOnet*, iNemsoft, Hytera and others.

The VCC-3™ has many unique features geared for use in LMR applications. Features include: ports for Plantronics PTT Mono or Stereo headsets, PTT Telephone handset, footswitch and built in gooseneck microphone. The VCC-3 provides intuitive controls for speaker & Headset volume, phone / headset inter-op & PTT. The large PTT button provides a 'hot key' or "Gamer" sequence to the software application to actuate press to talk functions. The "hot key" or "Gamer" sequence can be factory customized upon request. The VCC-3 utilizes Windows™ standard USB audio drivers. Telephone Handset switch over in Stereo Headset mode. The VCC-3 is an easy to setup & easy to use inter-operability tool with high quality audio and numerous integration features and options.



Standard Features

- USB Command Console, integrates with the Soft Dispatch systems from Motorola Solution, SmartPTT, iNemsoft, *TRBOnet*, Skytec, Hytera and others.
- Single 2-way audio talk channel
- Integrates with Plantronics PTT headsets
- ETC Foot switch & PTT handset functionality
- Intuitive controls for mode operation
- Left & Right Volume controls for connected Stereo speakers
- PTT button provides "hot key" or "Gamer" sequence, for mouse free operation
- 19" Close Talking Gooseneck Microphone
- Supervisor Headset Option
- Record In/Out Option
- Rugged Metal design

Technical Specifications

- Frequency Response: 200Hz- 9kHz
- Distortion: < .1%
- Analog output range: -40 dB to +8 dB
- Headset/Handset Impedance: Rx-10kOhm, Tx - 50 Ohm
- USB 'B' style connector & USB powered
- 3.5 mm jacks for PC speaker & foot pedal connectivity
- 350mA Nominal Current Consumption
- Size: 6.25" W x 2" H x 8" D
- Weight: 42 ounces
- 6 BTUs Per Hour Output

A Veteran Owned Small Business

