

VCC-2™ USB Desktop Station

Overview

The VCC-2™ is the mini version to the larger VCC-3 Command Microphone Console designed for use with inter-operability software dispatch consoles such as Motorola Solutions, SmartPTT, AVTEC, *TRBOnet*, Skytec, Hytera and others

The VCC-2™ features include: ports for integration with commonly available: Plantronics Mono PTT headsets, PTT Telephone 6 wire handset, ETC Foot switch and the built in gooseneck microphone. The VCC-2 provides intuitive controls for Left & Right speaker volume adjustment, & a large Microphone PTT Button. The large PTT button provides a “Hot Key” or “Gamer” sequence to the software application, actuating the press to talk function. The “Hot Key” or “Gamer” sequence can be factory customized upon request. The VCC-2 utilizes Windows™ standard USB audio drivers.

The VCC-2 is an easy to setup & easy to use inter-operability tool with high quality audio, numerous integration features and it is half the size of the VCC-3.

Standard Features

- USB Microphone console, designed to operate with the Soft Dispatch Systems from Motorola Solutions, , SmartPTT, AVTEC, *TRBOnet*, Skytec, Hytera and others
- Single 2-way audio talk channel
- Integrates with Plantronics Mono PTT headsets
- Foot switch & PTT handset functionality
- Left & right Volume controls for connected Stereo PC speakers
- PTT button provides “hot key” or “Gamer” sequence, for mouse free operation
- 19” Close Talking Gooseneck Microphone
- Made of Rugged Metal with a compact design

Technical Specifications

- Frequency Response: 200Hz- 9kHz
- Distortion: < .1%
- Analog output range: -40 dB to +3 dB
- Headset/Handset Impedance: Rx-10kOhm, Tx - 50 Ohm
- RJ-25 for PTT headset/handset connectivity
- USB ‘B’ style connector & USB powered
- 3.5 mm jacks for PC speaker & foot pedal connectivity
- 350mA Nominal Current Consumption
- Size: 6.25” W x 2” H x 8” D
- Weight: 20 ounces
- 6 BTUs Per Hour Output

